(AN-HP-Biolis. EN rev 2022.07.26)



## **General Information**

## Intended use:

H. pylori Turbilatex is a latex turbidimetric **assay only for the quantitative detection of** *Helicobacter pylori antigen* **in human stool samples** (not to be used for body fluid as blood, serum, plasma, urine, cerebrospinal fluid, oral fluid, synovial fluid or empyema fluid). This assay is simple and widely applicable.

For professional in vitro diagnostic use only.

H. pylori Turbilatex can be performed on every open chemistry analyser. Please follow the subsequent instructions in order to assure performance characteristics as describes in the instructions for use. This instruction has been validated by CerTest BIOTEC S.L. Laboratories.

Additionally, please read the "Instructions for use" for instructions on operating and programming user defined test.

### Reagents: Materials provided by CerTest BIOTEC S.L.:

Reagents	Quantity	Code							
Turbidimetric reagents (R1 & R2)	R1: 2 vials, 2x33 mL	TL-022HP01							
200 Det/kit	R2: 1 vial, 1x7 mL	TL-022HP02							
Auxiliary Reagents									
Calibration kit	Calibrator: 6 vials, 6x1 mL.	TL-022HP70, TL-022HP71 TL-022HP72 TL-022HP73 TL-022HP73 TL-022HP74 TL-022HP75							
Controls kit	Control C1, 2 vials, 2x1 mL/vial. Control C2, 2 vials, 2x1 mL/vial.	TL-022HP08 TL-022HP09							
Sample dilutions vials	1x2 mL/vial 1x2.4 mL/vial	MST-0014MP MST-0020P							

### Preparation of reagents:

R1 and R2 are ready to use.

Calibrators are ready to use

Controls are ready to use.

### Storage and stability

Kit components must be stored at temperature indicated on the label. Do not freeze.

Reagents are stable up to the expiration date printed on the label, always considering that reagent containers must be properly closed to avoid any contamination, must be kept away from the sunlight and conserved at temperature indicated on the label of each reagent.

### Specimen:

Collect enough quantity of human stool samples. These samples should be collected in clean and dry containers (no preservatives or transport media). The samples can be stored in the refrigerator (2-8°C) for 7 days prior to testing. Homogenise stool samples as thoroughly as possible prior to preparation.

The sample dilution vial with diluted sample can be stored for 7 days in the refrigerator  $(2-8^{\circ}C)$  prior to testing.

Use H.pylori Turbilatex stool collection tubes for sample collections described the instructions for use.

## Assay procedure

### Application parameter set up:

Specific analyzers settings for H. pylori Turbilatex must be programmed onto the analyzer, see below. For instructions, consult the Biolis 24i/50i (Tokio Boeki) analyzer manual and instructions for use provided with the kit.

### Loading of reagents:

Load reagents according to the Biolis 24i/50i (Tokio Boeki) analyzer manual.

### Calibration curve establishment:

A 6 point calibration curve can be established in Biolis 24i/50i (Tokio Boeki) analyzer. For instructions consult analyzer manual.

### Calibration stability:

Calibrate the system at least once a month is extremely recommended. Recalibrate the system when reagent lot is change or when the controls are out of the assigned range given in the control labels and CoA.

### QC controls:

H. pylori Turbilatex controls C1 and C2 must be assayed each day before running patient faecal sample extract to validate the calibration curve. The controls have assigned value ranges indicated on the label and certificate of analysis supplied. The control measurements must be within the indicated value range to obtain valid results for patient faecal extract. If the control values are out of range, follow next procedures: 1) Repeat QC control measurement, 2) Repeat calibration measurement.

### Results:

The results are evaluated automatically by the analyzer and presented in ng H.pylori antigen/mL.

Performance characteristics

Page 1 of 4

## H. pylori Turbilatex, Biolis 24i/50i, Tokyo Boeki (AN-HP-Biolis. EN rev 2022.07.26)



The following results have been obtained during the validation of H.pylori Turbilatex on the Biolis 24i/50i (Tokio Boeki) analyzer.

### Linearity:

H. pylori Turbilatex on Biolis 24i/50i analyzer using calibrator kit is linear in the calibration range of 0-40 ng H.pylori antigen/mL.



### Measuring range:

H.pylori Turbilatex assay measuring range is 0.8-40 ng H.pylori antigen/ml on the Biolis 24i/50i (Tokio Boeki) analyser. Samples higher concentrated than 40 ng H.pylori antigen/mL of stool must be diluted for proper quantification by the user, using additional sample buffer.

#### **Prozone effect**

Using the reported parameters, no prozone effect (hook effect) was observed up to 0.2 mg *H. pylori* antigen/mL of stool. Samples with H. pylori antigen concentration of 0.2 mg H. pylori antigen/mL give a typical positive result >40 ng H.pylori antigen/mL.

### **Detection limit**

**Limit of detection (LOD): 0.8 ng H. pylori antigen/ml.** The lower limit of detection of H. pylori Turbilatex was determined on 20 samples and 2 sample replicates as the mean value + 2xSD.

Limit of quantification (LOQ): 1 ng H. pylori antigen/mL. The lower limit of quantification is defined as the lowest actual amount of analysis that can be reliably detected; imprecision is < 20% as CV% on the Biolis 24i/50i (Tokio Boeki) analyzer.

Precision

H. pylori Turbilatex was tested with three different controls levels.

	Low	Medium	High		
	(1 ng/mL)	(10 ng/mL)	(40 ng/mL)		
N	20	20	20		
Mean (ng/mL)	1.08	10.23	39.76		
SD (ng/mL)	0.12	0.79	2.01		
CV (%)	11	8	5		

## Method comparison

Results obtained with H. pylori Turbilatex on the Biolis 24i/50i (Tokio Boeki) analyzer were compared with an immunochromatographic test (CerTest H. pylori, CerTest). The results were as follows:

	Sensitivity	Specificity
H. pylori Turbilatexvs CerTest H. pylori	86.5%	>98%

### **Shipping damage**

Please notify your distributor, it this product was received damaged.

## Symbols key

IVD	For in vitro diagnostic use only	Ĵ	Keep dry
<b>•••</b>	Consult instructions for use	×,	Temperature limitation
REF	Catalogue number	LOT	Lot number
$\searrow$	Use by	***	Manufacturer
Σn	Contains sufficient for <n> test</n>	DIL	Sample diluent
漱	Keep out of the sunlight		

## Manufacturer

### CERTEST BIOTEC S.L.

Pol. Industrial Río Gállego II,Calle J, Nº 1, 50840, San Mateo de Gállego, Zaragoza (SPAIN) www.certest.es

### NOTES

Please refer to the instruction for use for the detailed information about the test on the following:

Synthesis; Principle; Precautions; Reagents; Specimen collection and preparation; Interpretation of results and limitations.

Page 2 of 4



Biolis 24i/50i (Tokio Boeki) / Application parameters

ASSAY PARAMETERS	
Std. No	6
R1	305 µL
Sample	15 μL
R2	25 μL
Others	NA
Reaction mode	Endpoint
Primary wavelength	450 nm
Secondary wavelength	800 nm
Direction	Increase
Reagent blank lecture	33-34 cycle
Final lecture	51-52 cycle
Reaction time	10 min
Linear range	0-40 ng/ml
CALIBRATION	
Calibration Method	Linear
Calibration Method Calibration set	Linear 5 calibrators + Blank
Calibration Method Calibration set Blank	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml)
Calibration Method Calibration set Blank Calibrator 1	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 4	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 4 Calibrator 5	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 4 Calibrator 5 STEPS	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 4 Calibrator 5 <b>STEPS</b> Addition R1	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 4 Calibrator 5 <b>STEPS</b> Addition R1 Addition Sample	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 4 Calibrator 5 <b>STEPS</b> Addition R1 Addition Sample Incubation	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 3 Calibrator 4 Calibrator 5 <b>STEPS</b> Addition R1 Addition Sample Incubation Addition R2	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 3 Calibrator 4 Calibrator 5 <b>STEPS</b> Addition R1 Addition Sample Incubation Addition R2 Blank Lecture	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)
Calibration Method Calibration set Blank Calibrator 1 Calibrator 2 Calibrator 3 Calibrator 3 Calibrator 4 Calibrator 5 <b>STEPS</b> Addition R1 Addition Sample Incubation Addition R2 Blank Lecture Incubation	Linear 5 calibrators + Blank Calibrator 1 (0 ng/ml) Calibrator 2 (2.5 ng/ml) Calibrator 3 (5 ng/ml) Calibrator 4 (10 ng/ml) Calibrator 5 (20 ng/ml) Calibrator 6 (40 ng/ml)

# H. pylori Turbilatex, Biolis 24i/50i, Tokyo Boeki



(AN-HP-Biolis. EN rev 2022.07.26)

Spintech 240 Premium			FINAL	TEMP-OK	Salir
Menú de rutina Calibración QC F1 F2 F3	Reactivo F4 Parametr	• Voperación	simpi Si	istoma Mar	ntenimiento
MANINE .	11/1//	F	-monitor	Info. Reactivo	
1	111	Ciclo Sam	.ID arametri	Ciclo Samp.ID	arametri
	RI	1	3	1 6	_
- B2.		2	No.	2	-
- me		4		2	
· · · · · · · · · · · · · · · · · · ·	Prt 1	5	3	5 5	
· · · · · · · · · · · · · · · · · · ·		R1	3	6.	
1111.		7	3	7.	_
		8	3	B.	-
		10	4		-
	and the second se	11	4	1	
	C B2 13 S28 com	S	4	2.	
		MI	4	3 3	
	S3 a) 53 ct of S25	MI	4	4.	-
	S 832 08 S24	16 10	-		
🖿 + 🛛 🖬	S #33 CH S23	17		7 9	
📁 * 💴 📁	S III C II S22	18 .	4	8.	
📁 <sup>10</sup> 🔭 📁	<b>a</b> a <b>a a a</b>	19 9	4	9.	
		20 .	5	0.	
		21 .	5	1 1	-
	5 11 11 TH	22 .	5	2.	-
		24	5	4	
1 10 10 10 10 10 10 10 10 10 10 10 10 10	"On on of of	25 .	5	5 0	
		26 .		1	
		27 7	5	2	
Paro muestreo Urgancia	Lista de errores Arch Resultados	28 .	5	8	-
		30	6	D	-
Monitor Pedido R & E F5 F6 F7	R - Mon F8 F9	ado Ini	ciar In 10	iciar QC F11	E.Stop F12
				Fin	al

Spintech 240 Prer	nium				S.STOP	TEMP-OK	alir Salir
Menú de rutina F1 F2	n QC Reactivo F3 F4	Parametro			i Si	stema	Mantenimiento
No. Parametre	Nombre parar H.Pyl 1	ombrecompl H.Pylor	1			0	ptica
Información Datos		Calibrac	ión				
Unidades	ng/ml	Tipo		Sp	line1		~
Decimales	3				Std.Conc.	Auestra	
			#3	10	24	2.0 #2	40
Analisis			#6				
Тіро	Punto Final: Abs principal fuera V	Estabil	idad Ca	II <mark>0</mark>			
Longitud de onda princ	1,450nm ~						
Longitud de onda Sub	800nm ~						
Metodo		Tamaño	Botell	a (ml) —	26.5		
Correlación		REACTIVO	ametro M	60	REAC	TIV01	10
	Pendiente Intercepción	REACTIVO	02 R1	40	REAC	TIVO2 R1	5
Y =	1 * X + 0	REACTIVO	02 R2	20	REAC	TIVO2 R2	3
Borrar		Próxima página	-	opia	Imprin	nir G	uardar
			sec	uridad			
Monitor Pedido F5 F6	R & E F7 F8	Preparado F9		Iniciar F10		iciar QC F11	E.Stop F12
	Paro de muestreo						

Menú de rutina F1	Calibración F2	m QC F3		Reactivo F4	Parametro	peración s	S.STOP	Sistema	Mantenimiento
No. Parametro	21 ~	Nombre	parar H.Pyl 1	Nor	nbrecomp <sup>(H.Pylori 1</sup>				Optica
Aspiración					Datos a pro	cesar			
Clase		Individual	Oble		Leer			Iniciar	Final
Vol.	Clase	Vol.	Unidades				Principal	51	52
	Muestra	15	ul				Sub	34	35
	Reactivo 1	305	ul				Bajo		Alto
	Reactivo 2	25	ul		Abs. Limite		-3	3	
Pantalla R	• eacción	Blanco Agua	<ul> <li>Blanco R</li> </ul>	eactivo	Correccion Limite Punt Comprobar	en blanco o Final Linealida	d (%)	3	
Nivel 0 Pu	untos	1			Chequeo Pr	ozona			
Extensión		3				Iniciae	Final	Limite (9)	1
Extension					Primero	ancia	T IIIGI	Enning (Ap	
					Serundo				Ato Baio
Borrar Monitor F5	Pedido	R & I	Págin : F	na Anterior R - Mon F8	Próxima página Preparado F9	Inici	iar	primir Iniciar QC F11	Guardar E.Stop F12
		-							
		Dara da	muostro	•					

Page 4 of 4